BILMAK GUVENLIK TEKNOLOJILERI A.S. www.bilmak.com.tr

Add: Hurriyet Mah. Yurt Sok. No:38 Kat:5-6 Kagithane-Istanbul Tel:0212. 225 80 50 Fax: 0212. 234 46 02 e-mail:bilmak@bilmak.com.tr



ORBITA TECHNOLOGY CO.,LTD

Add:Orbita Industrial Park, Changbuviifage, Xinxu Town, Hulyang Distric, Huizhou City, Guangdong Province, China Tel:86-752-3633501 Fax:86-752-3633600 Mail::sa1es3.hz@orbitatech.com Mobile:86-15282149613

Website: www.orbitatech.com www.orbitalock.com













ISO 9001:2008



COMPANY PROFILE

Orbita is a reputable hospitality products manufacturer with ISO certified 46,000 square meters garden factory, established to offer the best quality products with professional and effective service to our customers.

Orbita series of products including hotel card locking system, hotel in room safe, hotel minibar, touch screen switch, hotel in room telephone, cabinet locker, smart hotel room system and other hotel in room accessories, are products of years of experience integrated with advanced technologies from Siemens, Dallas, Atmel, Philips etc. Orbita locking system certified by Opera Fidelio and other popular PMS system, has just enabled Orbita products to a wide range of compatibility.

In fact, all of ORBITA products are CE, FCC, RoHS marked and ORBITA is one of the few brands in this industry that passed 800,000 times BHMA standard circling test. Regional standard like SASO, SONCAP, SIRIM are also available with all Orbita products.

More than 10,000 hotels, service apartments, resorts, university dormitories, hospitals and cruise ships covering 100countries in the world are using Orbita card locks, digital safes, minibars, touch screen switches and other satisfactory hotel intelligent accessories. Our customers include most popular international hotel management groups such as Accor, Marriot, Carlson, Hilton, Starwood, Intercontinental, Kempinski, Crow Regency and other regional hotel management groups. Moreover, Orbita is also offering OEM & ODM services for many leading Europe and American brands in this industry.

ORBITA believes that every customer is a customer for life, manufacturing products of fine quality with our experience and knowledge is our source of pride and customer's satisfaction is our only criterion in service.



















Contents

Company Profile	2
Orbita One Card System Configuration	5
Orbita RFID Access	6
Orbita Split Model	8
Orbila Waterproof Model	10
Lockcase Options and Specifications	14
Lock Installation Diagram	15
Orbita Bathroom Lock	16
Orbita Cabinet Locker	17
Orbita Guest room control system	18
Energy Saving Switch	20
Lift reader&Controller	21
Door Signage	22
Bedside Console & touch screen panels	23
Orbita Hotel Room Safe	24
Orbita Hotel Minibar	26
Orbita Hotel Telephone	28
Successful References	30

Orbita One Card System Configuration







FUNCTIONAL CHARACTERISTICS

Interface wilh most of the PMS systems, FtdellOIOpera registered!

c e & FCC Certified!

Brushed stainless steel color lasts more lhan10 years

ANSI Standard mortise

Inside Dead Bolt. Inside handle retracts latelies and deadbolt.

Mifare 1K card. compatible with Mifare Energy Saver

Override Computer Key for Emergency use, Individual or master cyfinder

Lost guest card suspension simply by issuing a new guest card with suspending function

Lock operation record printable: 240 pcs or more

Power: 4pcs #5 AA Alka/Jne batteries. 18 months' duration

Low battery voltage warning (Lower than 3.5 V,)

Self Error detecting by LED and ·beep•

Improper lock warning

Passage function available

Can be integrated with 16 public areas such as Lift/Parking/Swimming Pool/Sauna Room/Tennis



Orbita Split Model









Valuable Features:

Sliding reader with hidden cylinder Elegant, fashionable.









TECHNICAL PARAMETERS		
Dimension of External Panel.	L9Smm·ws2mm·1-126.8mm	
Material:	StRmless Sleel, Mo1s1ure Proof Fire Re1ardant	
Working Voltage:	DC6Vor4 AAAAlkahne battenes	
Power Consumption:	Static Load<10Ua Dynamic Lood 100-150Ma	
Working Environment:	W01king Humiclily: 20%-90% Working Tompernturc -SQL-60'C	
Keycard OptiOn-	RF Temic card, M1fare I card, UHra-hght card	

FUNCTIONAL CHARACTERISTICS

Interface with most of the PMS systems, Fidelio/Opera registered!

CE & FCC Certified!

Stainless steel cotor lasts more than I 0 years

ANSI **mortise**, European Standard mortise 72mm/85mm hole distance. Anlt-panic type **1s** also available

Mortise thickness 18mm. strike thickness 22mm

No electronic Inside mortise.

Inside Dead Solt.

Tamie and Mifare card, 100,000 times life, high security. compatible with Energy SaYer.

Override Computer Key for Emergency use, Individual/mas1er cylinder

Personalized Locking System and cylinder cover

Step by step Installation software. easy operation, OEM locking system

Classfi ed Access Authorization for safety management.

General master card. building master card, Ocor master caret guest card. Fire-

All card with valk:lity. guest card expires automatically at default check out date and time

Meeting room function and three levels of passage door functions.

Lost guest card suspension simply by issuing a new guest card with suspending function

Multiple operators with different card Issuing authonzatton

Lock operation record printable. 240 pcs or more

ReceptionIst card issuing records printable

Power:4 pcs #7 Alkaline battery. 14 months' duration

Low Bauery Voltage warning. (Lower than 3.5 V.)

Self Error detecting by LEO and 'beep-.

Improper lock warning

Wireless stand alone lock realizes 95% or on line lock function.


Can be Integrated with UflJParking/Sw1mmmg/Sauna Room/Gym access ... etc(One card system)

Orbita Waterproof Model









Valuable Features:

Waterproof design

Complete 304 stainless steel material

Sealed electronics.





TECHNICAL PARAMETERS		
Dimension of External Panel.	L290mm"W60mm·H34mm	
Material:	StRmless Sleel, Mo1s1ure Proof Fire Re1ardant	
Working Voltage:	DC6Vor4 AAAAlkahne battenes	
Power Consumption.	Static Load<10Ua Dynamic Lood 100-150Ma	
Working Environment:	W01king Humidily: 20%-90¾ Working Tompernturc -SOI60°C	
Keycard OptiOn-	RF Temic card, M1fare I card, UHra-hght card	

FUNCTIONAL CHARACTERISTICS

Interface with most of the PMS systems, Fidelio/Opera registered OE & FCC Certified!

Stainless steel color lasts more than 10 years

ANSI standard mortise, European Standard mortise 72mm/85mm hole distance Inside deadbolt. Inside handle retracts latches and deadbolt

RF Tamle card, Mlfare 1 card, Ullra-hight card are optional, compatible with its own energy saver

Override Computer Key for Emergency use, Individual or master cylinder

Personalized locking system and cylinder cover

Step by step installation software, *easy* operation, OEM locking system available

Classified Access Authorization for safety management

General master card. building master caret floor master card. guest caret Fire alarm card

All cards with validity, guest card expires automat1cally at default check out date and time

MeetJng room function and three levels of passage door functions

Lost guest card suspension simply by Issuing a new guest card with suspending function

Multiple operators with different card issuing aulhori?ations

Lock operation record printable: 240 pcs or more

Receptionist card Issuing records printable

Power: 4pcs #5 AA AJkaline batteries. 18 months' duration

Low battery voltage warning (Lower than 3.5 V.)

Self Error detecting by LED and "beep"

Improper lock warning

Wireless stand atone k>dk realizes 95% of online lock function

Passage function available

Can be integrated with 16 public areas such as Utt/Parking/Swimming Pool/Sauna Room/Tenms court/Gym ... etc. That is to say, one Guest card not only can open its own Guest room but also can open other common areas such as Lift. Parking, Club, Swimming ... etc optionally (such as if the guest pays for lift, Parking, Club, Swimming ... etc, his Guest card can open its own Guest room and Lift, Parking, Club, Swimming ... etc; if not, his Guest card can only open its own Guest room). Also it is suitable for suite Guest room

















- * Wireless
- * Program locks
- ★ Update clock
- * Read & download openings
- * Open locks as master key

TECHNICAL PARAMETERS Dimension of External Panel Material: Working Voltage: Static Load<10Ua Dynamic Load 100-150Ma Consumption. Working Humidity: 20%~90% Working Temperature: -50 ℃ -60 ℃ Working Environment: Keycard Option:

FUNCTIONAL CHARACTERISTICS

Interlace with most or the PMS systems, Fidelio/Opera registered! CE & FCC Certified!

Stainless steel color lasls more than 10 years

ANSI standard mortise

Inside deadbolt. Inside handle retracts latches and deadbolt

RF Temic card, Mifare 1 card. Ultra-light card are optional, compatible with Its ovm energy saver

Override Computer Key for Emergency use, Individual or master cylinder

Personalized locking system and cylinder cover

Step by step installation software, easy operaUon. OEM locking system available

Classified Access Authorization for safety management

General master card, building master card, floor master card, guest card, Fire-

All cards with validity, guest card expires automatically al default check out date

Meeting room function and three levels of passage door functions

Lost guest card suspension simply by issuing a new guest card with suspending

Multiple operators with different card issuing authorizations

Lock operaUon record printable: 240 pcs or more

Receptionist card issuing records printable

Power: 4pcs #SAA Alkaline batteries. 18 months' duration

ow battery voltage warning. (Lower Ihan 3.5 V.)

Self Error detecting by LED and "beep"

Improper lock warning

Wireless stand alone lock realizes 95% of online lock function


Passage function available

Can be integrated with 16 public areas such as Lift/Parking/Swimming Pool/Sauna Room/Tennis chut/Fym...etc. Thal is to say, one Guest card not only can open its own Guest robmbut also can open of the roommon areas such as Lift, Parking, Club, Swimming, etc. optionalty (such as 1 the guest pays for Lift, Parking, Club, Swimming, etc. in the Luest card can open its own Guest room and Lift, Parking, Club, Swimming, etc. in the Luest card can open its own Guest room and Lift, Parking, Club, Swimming, etc. in the Luest card can open its own Guest room.) Also it is suitable for sole

Lockcase Options and Specifications


Model: M01 Model: M06 Model: M10 Model: M11

Lock Installation Diagram




Important Tips:


- Don't use deadbolt as door stopper,th1swlll cause serious problem if deadbolt is damaged or bent.
- Make sure enough space is left for any part of the lock. It is extremely prohibited to hammerinthe mortise or the screws. Use a knife, saw or file to fix the hole to make sure the mortise can go inside smoothly. Making sure the spindles or cylinder does not hit any wood.
- Make sure the hole for the latch is deep enough and no burr left inside, when the latch hit the wood or burr, continuous alarming will be activated.
- Adjust and rix the cyhnder properly for emergency use.
- Be careful with the cable during installation. Any cable breaking will result in malfunction.
- · The deadbolt knob should be upright not horizontal.



Orbita Bathroom Lock







Orbita Cabinet locker








Orbita Guest room control system

Application system diagram






Linghting control:on/off/dlmming/scene A/C control: valve/Fan speed Curlain control/TV control. Door/safe/ window status monitoring. Guest/staff in room identification. Pc software /app for I pad.mobile phone.

Network switch Hotel management serve The host-o-repfing accommens manifestered computer I'l e 111:1,nextility name emell computer The Meurity management b-motifn's

Network diagram



TCP/IP

CAN BUS

Lift reader&Controller


Room only type

Size	86mmx86mm
A/C	220V
Mifa	re 13.56mhz
Only	specific room card can get power
Nam	e card can not get power

Frequency type

Size:86mmx86mm
A/C 220V
Milare 13.56mhz
Any mlfare card can get power
Name card can not get power

3 Phase type










ESS-20

ESS-40

ESS-70

Energy saver with don't disturb and make up room





ESTP-01

Lift reader





MFR-01

MFR-02

Lift controller



MFC-03

FEATURES

Show guest card, go directly to the guest floor. Show staff card, activate all buttons No card can not access Public floor Emergency or damage, recover lift default function.

Door Signage



DS-358HR



DS 258HR



DS-201HP



DS-200HS



DS 202HS



DS-200UP



DS 201HG



Bedside Console & touch screen panels



TSS-41S



TSS-42S



BC-13B



BC-20B



BC-18G



BC-11G



TSP-01S



TSP-02S

Orbita Hotel Room Safe



OBT-2045MB: H200"L450'0400mm

OBT-2043MB: H200'L430'0370mm OBT-2040MB- H200"L400'0300mm

OBT-2031MB : H200"L310'D200mm




OBT-2045ME. H200"L450'0400mm

OBT-2043ME: H200'L430'0370mm

OBT-2040ME. H200"L400'0300mm

OBT-2031ME: H200"L310'0200mm



5 mm Cold-Rolled Steel Door Two 3/4 inch (19 mm) Diameter Steel Locking Bolts Scratch-Resistant Powder Coat Finish

FEATURES

Enhanced LED Display

Audio/Visual Operating Signals

Opening: Two sets of password operation- 4-digit guesl password/ 6-digit master password/ 6-CEU password(Optional) and override key

Event audit trall(Oplaional)

Easy Access Battery Panel

Emergency Battery Jumper Box

Secure Pedestal Mounting

Mechanical Fall-Safe Override Key

Tamper-Proof Installation Hardware

Spring to a door

Axing t)oleS at bottom and back with screws

mode (3 times wrong input of code gets frozen for 15mins)

OTHERS

Warrw,IY'.1 year Batte,) ... 4AA Low Bat ery warning Batteries m_{clude}



OBT-2045MA: H200"L450'0400mm

OBT-2043MA: H200'L430"D370mm

OF PERSONAL

OBT-2040MA: H200"L400"D300mm

OBT-2031MA: H200"L310'0200mm

CONSTRUCTION

5 mm Cold-Rolled Steel Door Two 314 inch (19 mm) Diameter Steel Locking Bolts

Scratch-Resistant Powder Coat Finish

FEATURES

Enhanced LED Display

AudioNisual Operating Signals

Opening: Two sets of password operation-- 4-digil guest password/ 6-digil master password and override key

Easy Access Battery Panel

Emergency Battery Jumper Box

Secure Pedestal Mounting

Mechanical Falt.Safe Override Key

Tamper.Proof Installation Hardware

Inner carpet

Spring loaded door

Flying holes at bottom and back with screws

Auto secure mode (3 times wrong input of code gets frozen for 15mlns)

OTHERS

Warranty: 1 year Batteries \$4AA

Low Battery wamtr

Batteries IndU⊲ed

11 OBT-4035CT: H130"L400"0350mm

CONSTRUCTION

5 mm Cold-Reled Steel Door

Two 314 inch (19 mm) Diameter Steel Locking Bolts Scratch-Resistant Powder Coat FJnish

FEATURES

Enhanced LEO Display

AudioNisual Operating Signals

Opening: Two sets of password operation/4-digit gues password/ 6-digit master password and override key

Easy Access Battery Panel

Emergency Battery Jumper Box

Secure Pedestal Mount,ing

Mechai, Ical Fall-Safe Override Key

Tamper-Proof Installation Hardware

InnerTet

Spring 1oaded door

Floring holes at bottom and back With SClews

Auto sbre mode (3 hmes wrong input of code f/ozen rbr 15mlns)

OTHERS

Warranty: ryear

Low Battery warning

Batteries included

Orbita Hotel Minibar



MB-30X



MB-30DX



MB-406B



MB-40GB



MB-60BA



MB-SOGA

Model	MB-25	MB-30	MB-40	MB-60
Cooling Method,	absorption	absorption	absorption	absorption
Storage Temperature("C),	0~12	0~12	0~12	0~12
Input Power(W),	65	65	65	85
Energy Consumption(kwh/24h),	0.9	0.9	0.9	1.2
Validity Capacity(L),	25	30	40	60
Voltage(V),	AC220	AC220	AC220	AC220
Type of Controller	Digital	Digital	Digital	Digital
Type Of Door Seal:	Removable	Removable	Removable	Removable
NeVGross Weight(kg),	16/18	16.5/18.5	18.5/20.5	21/21.5
Shape Size(w•o•H)mm,	380*400*480	400*420*517	400*470*517	482*480*521
Packing Size(W•D•H)mm,	460*480*545	460*450*560	460*500*560	530*510*600

Outstanding features;

Cool&qulet

High performance with/a uperior absorption new technology Cooling by amm onia, no moving part. no compressor, no fan No vibration. no noise (0 db) maintenance-free&long life.

Orbita Hotel Telephone



HT-1001



HT-1003



HT-1005



HT-1006



HT-1008

Professionally design	ed panel whh hotel name and logo primed available
One-touch button(+ 10). ,5. · J. ·O)
14 digits memory	
Duel loneselec1ron1c	ringing and volume 2 levels adjustable
Auto re-dial	
Dest and wall mountal	ble
Thunder-proof and Ar	ntl_EMI design
Waterproof and moist	ure proof

Professionally de	signed panel with hotel name and logo printed avail1able
One-louchbutton	(+10. •5. +3 ·O)
Large message lig	ght, voice message e)(lf8C1ion
Dual tones electro	onic ringing and volume 2 levels adjustable
Storage key-mem	ory funcation
Auto re-dial	
Oest ano wait mo	untable
Thunder-proof an	d Anti EWI design
Waterproof and m	noisture proof.

One-touchbu	non(+10, •5. •3. O)	
14 d'Iglis mem	ory	
Dual tones ele	ctronic ringing	
Speaker volur	e HULow adjustable.	
Oest and wall	mountable	
Thunder-proo	and Anli EMI design	

Pr	roless1onally designed panel wllh hotel name and logo prinled a11altable
O	ne-touch bunon(+IO, °5. ·3. ·0)
16	digits numbers LCD dispity
St	torage Set up
Αι	uto re-dial
O	est and wall mountable
Th	nunder-proof and Anll_EMI design
w	aterproof and molslure proof

Professionally	designed panel with hotel name and logo printed available
One-louchbu1t	on(+tO. •5 •3 •0)
14 digils memo	у
Dual tones elec	trome ringing
Ringer Indtcata	light
Dest and wan n	ountable
Thunder-ptool	and Ant EMI design
Weterprool and	moisture prool





HT-1009B



HT-1010



HT-1011



HT-1012

Prolessionally designe	d panel with hotel name and logo prinled available
One.fouch bullon(*10	5, •3. •0)
14 digils memory	
Duat tones etecuonic r	inging
Auto re-dial	
0es1 and wall mountab	le
Thunder-proof and Ant	i_EMI design,
Waterproof end moistu	re proof

Professionauy des	s!glie-d panel with hotel name and logo print&d available
On&·lOuchbu11or	n(40 tS. ·3. •0)
La,ge message U	ghl, voice meHage &lClraclion
Dual lones electro	nlc mgm_g
Take-up automati	cally
Auto re-dial	
Oest and wait mou	untable.
Thunder-proof ario	d Anl!_EMI design
Watermroof and m	Olekum nmof

One-louch button(•10	s. •3. ·O)
14 diglls memory	
Dual lones elec11onlc ririg	mg and volume 2 levels adJuslable
Auto re-dial	
Oest and wan mountable.	
Thunder-proof and AnU_E	EMI design ,
Walerproof end moislUre	proof

Human englneenng mechan,cs ptoJect of handle	
Sofl humanized ting	
Beautiful and emc1enl u\$elul ring-coming tight	
Double audio diatmg	
Aulometic redtal	
High Immunity 10 electro-magnetic: radiation	
Walerprool and mo!Slure proof.	

International fashion design apperance.	
Human engineering m&ehamcs pr0jec1 of handle	
Sofl humanl:ted ting	
SOS emergency call key	
Aulomatic redial	
Oest and wall mountable.	
High Immunity to electro-magnetic radiation	
Walerprool and moisture prool	

Successful References

































































































Crown regency prince resort in Boracay, Ph